

Clean Water Pump

Economical Running

Our pumps assure superior combustion efficiency and minimize fuel consumption

Portability

Adopted special alloy frame, largely reduced the weight and assures simple use

A Wide Range

Excellent and advanced impeller ensures water supply in a wide range

Durable Construction

The principal parts of each pump are reinforced for superior wear resistance and corrosion resistance

Easy Maintenance

Cleaning the inside casing can be done simply by just removing a few bolts



Model	KDP20	KDP30	KDP40
Type	Diesel pump	Diesel pump	Diesel pump
Suction&discharge port diameter(mm)(in)	50(2")	80(3")	100(4")
Rated capacity(m³/h)	22.0	30.0	40.0
Rated total head(m)	15	13	16
Self-priming time(s/4m)	80	120	180
Max.suction head(m)	8.0	8.0	8.0
Rotation speed(r/min)	3600	3600	3600
Noise level[dB(A)/7m]	74.0	76.0	79.0
Overall dimension(mm) (L×W×H)	525×410×515	570×445×550	650×480×600
Net weight(kg)	38.5	49	62.5
Engine model	KM170	KM178	KM186
Rated power(kW)	2.8	4.0	6.3
Rated speed(r/min)	3600	3600	3600
Fuel consumption(g/kW.h)	288	285	281
Displacement(cm³)	211	296	406
Starter system	Recoil starter	Recoil starter	Recoil starter

YAMA

Diesel Water Pump 水泵 WSP80LSY



- 采用WS188FB柴油机，动力强劲，使用寿命长。
- 产品具有结构紧凑，重量轻，扬程高，油耗低等优点。
- 广泛适用在灌溉农田，花草园林和冲洗矿渣等，
为一款小巧灵便的机械化喷灌设备。
- Basic: Powered by WS188FB diesel engine, more powerful, long working life.
- Features: Compact structure, low weight, high-head, low consumption.
- Application: As one small creatures mechanized irrigation equipment,
widely be used for agricultral irrigation, gardens and flushing slag.

型号 Model		WSP150L/E
流量 Capacity	m ³ /h	137
	L/S	38
扬程 Head (m)		6.1
效率 Efficiency (η%)		80.5
进出水口直径 Suction/Discharge port dia (mm)		150
功率 Power (KW) (HP)		6.6 (9)
净重 Net weight (Kg)		200
转速 Speed (r/min)		1500
外形尺寸: 长×宽×高 Dimension: L×W×H (mm)		945×630×855
动力型号 Engine model		WS188FB (凸轮轴输出) (The camshaft output)