

## Impact Wrenches



AT-5061



AT-5040



AT-5056



AT-5041



AT-5042



AT-5044

| Model                          |        | AT-5061                | AT-5065                  | AT-5040                | AT-5041                 | AT-5042                | AT-5044                |
|--------------------------------|--------|------------------------|--------------------------|------------------------|-------------------------|------------------------|------------------------|
| Square Drive                   |        | 3/4"                   | 3/4"                     | 1/2"                   | 1/2"                    | 1/2"                   | 1/2"                   |
| Capacity Bolt Size             | inch   | 1"                     | 1"                       | 5/8"                   | 5/8"                    | 1/2"                   | 1/2"                   |
|                                | mm     | 25.0                   | 25.0                     | 16                     | 16                      | 13                     | 16                     |
| Free Speed Rpm                 |        | 4,800                  | 4,800                    | 7,000                  | 7,000                   | 9,000                  | 7,000                  |
| Max Torque                     | ft-lb  | 700                    | 700                      | 230                    | 230                     | 190                    | 400                    |
|                                | kgs-m  | 96.6                   | 96.6                     | 31.7                   | 31.7                    | 26.2                   | 55.2                   |
| Overall Length                 | in.    | 9½"                    | 9¾"                      | 7"                     | 7"                      | 5⅞"                    | 6¾"                    |
|                                | mm     | 241                    | 248                      | 178                    | 178                     | 149                    | 171                    |
| Air Inlet(Pt)                  |        | 1/4"                   | 1/4"                     | 1/4"                   | 1/4"                    | 1/4"                   | 1/4"                   |
| Air Inlet(Id)                  |        | 3/8"                   | 3/8"                     | 3/8"                   | 3/8"                    | 3/8"                   | 3/8"                   |
| Avg.air CONSUMPTION            | cfm    | 7                      | 7                        | 4.0                    | 4.0                     | 4.0                    | 4.0                    |
|                                | m³/min | 0.198                  | 0.198                    | 0.113                  | 0.113                   | 0.113                  | 0.113                  |
| Net Weight                     | lbs    | 10.6                   | 10.6                     | 5.3                    | 5.3                     | 2.9                    | 5.6                    |
|                                | kgs    | 4.8                    | 4.8                      | 2.4                    | 2.4                     | 1.3                    | 2.5                    |
| Work.air Pressure              | psi    | 90                     | 90                       | 90                     | 90                      | 90                     | 90                     |
|                                | kg/cm² | 6.5                    | 6.5                      | 6.5                    | 6.5                     | 6.5                    | 6.5                    |
| Packing Pcs/ctn/G.W./cuft(Kgs) |        | 4/Ctn/<br>21kgs./1.32" | 4/Ctn/<br>22.3kgs./1.32" | 10/Ctn/<br>25kgs/1.58' | 10/Ctn/<br>25.5kgs/1.6' | 10/Ctn/<br>24kgs/1.22' | 8/Ctn/<br>23.6kgs/1.2' |
| Sug Air Comp.(HP)              |        | 3                      | 3                        | 2                      | 2                       | 2                      | 2                      |

## Impact Wrenches



**YU-2570T8**  
Twin Hammer, with  
8" Anvil

## Riveters & Pull-Setters



AT-6015

| Model           | YU-2570T8                       |
|-----------------|---------------------------------|
| Square Drive    | 1"                              |
| Bolt Capacity   | 2" (50mm)                       |
| Max Torque      | 2500 FT-LB (345 KG-M, 3390 N-M) |
| Free Speed      | 3,000 R.P.M.                    |
| Air Consumption | 8.2 CFM                         |
| Air Inlet       | 1/2"                            |
| Air Pressure    | 90 PSI                          |
| Overall Length  | 622 mm (2"):453mm               |
| Net Weight      | 14.6 kg (2"):13.1 kg            |
| Air Hose        | 13 mm                           |

| Model                             | AT-6015            |         |
|-----------------------------------|--------------------|---------|
| Blind Rivet Setting Capacity(im.) | 3/16"              |         |
| Capacity Bolt Size                | lbs                | 1,586   |
|                                   | kgs                | 720     |
| stroke length                     | in                 | 9/16"   |
|                                   | mm                 | 14      |
| Overall length                    | in                 | 10 3/4" |
|                                   | mm                 | 273     |
| Air inlet(PT)                     | 1/4"               |         |
| Air Hose(ID)                      | 3/8"               |         |
| Avg.Air Consumption               | cfm                | 0.03    |
|                                   | l/min              | 0.85    |
| Net Weight                        | lbs                | 3.4     |
|                                   | kgs                | 1.5     |
| Work.air Pressure                 | psi                | 90      |
|                                   | kg/cm <sup>2</sup> | 6.5     |
| Packing Pcs/Ctn/G.W./Comp.(HP)    | 10/Ctn/19kgs/1.6'  |         |
| Sug.Air Comp.(HP)                 | 0.5                |         |